

ONTARIO

idea
ceramica

Dress Your Home

Pavimento



V2



PEI 4

ONTARIO

Gres Porcellanato
Porcelain stoneware
Grès cérame
Feinsteinzeug

30x120
12"x48"



RETTIFICATO / R9

20x120
8"x48"

FORMATO Size	SPESSORE Thickness	SCATOLE Boxes			PALETTE Pallets		
		pcs	m ²	kg	box	m ²	kg
30x120	9,5	4	1,44	28,60	30	43,20	880
20x120	9,5	6	1.44	28,60	36	51,84	1050

Imballi / Pesi
[Packaging / Weights]








30X120
20X120

Ontario

Gres Porcellanato / Porcelain stoneware / Grès cérame / Feinsteinzeug



30X120
20X120

Naturale

IONP50C Ontario NATURALE / 30x120 ■ 83



IONP05C Ontario NATURALE / 20x120 ■ 83

Miele

IONP30C Ontario MIELE / 30x120 ■ 83



IONP03C Ontario MIELE / 20x120 ■ 83

Grigio

IONP40C Ontario GRIGIO / 30x120 ■ 83



IONP04C Ontario GRIGIO / 20x120 ■ 83

Bianco

IONP10C Ontario BIANCO / 30x120 ■ 83



IONP01C Ontario BIANCO / 20x120 ■ 83

Skirting ■ 24
6,5x120



8 pz
15 Kg.




IONB05 BATT. Ontario NATURALE



IONB03 BATT. Ontario MIELE



IONB01 BATT. Ontario BIANCO



IONB04 BATT. Ontario GRIGIO

Vendita solo a scatole complete. To be sold as full box only.
Vendable uniquement en boites entières. Abnahme nur volle pakete.


Ontario

Gres Porcellanato / Porcelain stoneware / Grès cérame / Feinsteinzeug


Special pieces Pezzi speciali

30x120 / 12"x 48"

Gradino costa retta ■ 121



Angolare DX e SX ■ 129




Consigli di posa / Conseils de pose / Verlegeempfehlungen

Installation advise




NO 50%



Mix solution: 30x120 / 20x120

OK



Mix solution: 30x120 (60%) / 20x120 (40%)



CARATTERISTICHE TECNICHE

Technical features
Caractéristiques techniques
Technische Eigenschaften

PAVIMENTO

Floor tile

RIVESTIMENTO

Wall tile



Azienda
Company



idea ceramica // by MoMa ceramiche Group

	Metodo di prova Testing method Méthode d'essai Prüfmethode	Valori prescritti International Standard Internationale Normwerte Valeurs Prescrites	Valori prescritti International Standard Internationale Normwerte Valeurs Prescrites	Valori medi Average Value Mittelwert Valeurs Moyennes
Assorbimento d'acqua Water absorption Absorption d'eau Wasseraufnahme	ISO 10545 - 3	≤ 0,5 %	> 10 %	Conforme In accordance Entsprechend
Lunghezza e larghezza Length and width Longueur et largeur Länge und Breite	ISO 10545 - 2	+/- 0,6 %	+/- 0,5 %	Conforme In accordance Entsprechend
Spessore Thickness Épaisseur Stärke	ISO 10545 - 2	+/- 5 %	+/- 10 %	Conforme In accordance Entsprechend
Rettilineità degli spigoli Straightness Equerrage des angles Geradlinigkeit	ISO 10545 - 2	+/- 0,5 %	+/- 0,3 %	Conforme In accordance Entsprechend
Ortogonalità Rectangularity Orthogonalité Rechtwinkligkeit	ISO 10545 - 2	+/- 0,6 %	+/- 0,5 %	Conforme In accordance Entsprechend
Planarità Warpage Planéité Ebenflächigkeit	ISO 10545 - 2	+/- 0,5 %	+/- 0,5 % - 0,3%	Conforme In accordance Entsprechend
Coefficiente di attrito (scivolosità) Friction coefficient (slipperiness) Coefficient de friction (glissement) Reibungskoeffizient (Schlupfrigkeit)				
Coefficiente dilatazione termica lineare Coefficient of linear thermal-expansion Coefficient de dilatation thermique linéaire Lineare Wärmeausdehnung	ISO 10545 - 8	9 MK ¹		7 MK¹
Resistenza alla flessione Flexion resistance Résistance à la flexion Biegezugfestigkeit	ISO 10545 - 4	> 35 N/mm ²	> 15 N/mm ²	Conforme In accordance Entsprechend
Resistenza all'abrasione profonda Deep abrasion resistance Résistance à l'abrasion profonde Beständigkeit gegen Tiefenabrieb				
Resistenza al gelo Frost resistance Résistance au gel Frostwiderstandsfähigkeit	ISO 10545 - 12	Nessuna alterazione No alteration		Conforme In accordance Entsprechend
Resistenza agli sbalzi termici Thermal shock resistance Résistance aux écarts de température Temperaturwechselbeständigkeit	ISO 10545 - 9	Nessuna alterazione No alteration		Conforme In accordance Entsprechend
Resistenza dei colori alla luce Color resistance to light Résistance de la couleur à la lumière Lichtbeständigkeit	DIN 51094	Nessuna alterazione No alteration		Conforme In accordance Entsprechend
Resistenza ai prodotti chimici Chemical resistance Résistance aux produits chimiques Chemikalienfestigkeit	ISO 10545 - 13	Classe UB min	Classe GB min	Conforme In accordance Entsprechend
Resistenza alle macchie Stain resistance Résistance aux taches Flecken-Beständigkeit	ISO 10545 - 14	Classe 3 min	Classe 3 min	Conforme In accordance Entsprechend

UNI EN 14411 G
Gruppo BIa GL

Pavimenti in gres porcellanato
Porcelain wall and floor tiles

UNI EN 14411 L
Gruppo BIII GL

Rivestimenti in bicottura
Double firing wall tiles



Finale Emila (MO) - Via Panaria Bassa 17/A - Italy

Tel. +39 0535 90401 / info@ideaceramica.biz

www.ideaceramica.net

A detailed botanical illustration of various tropical plants, including large palm fronds with distinct horizontal stripes and clusters of bird-of-paradise flowers. The style is painterly and naturalistic, with a muted color palette of greens, browns, and blues.

idea ceramica

Via Panaria Bassa 17/A
41034 Finale Emilia (MO)

Tel. +39 0535 90401
Fax. +39 0535 762368

MADE IN ITALY

info@ideaceramica.biz

www.ideaceramica.net